

HAND-E ADAPTATIVE GRIPPER



*Excludes fingertips

START PRODUCTION FASTER



Extenders sold separately



Force Copilot sold separately

TAKE FULL CONTROL

50-MM STROKE GRIPPER IS SUITED TO COLLABORATIVE ROBOTS

ADAPT THE HAND-E TO YOUR PARTS WITH ACCESSORIES OR CUSTOM FINGERTIPS

UNLOCK FULL POTENTIAL WITH FORCE COPILOT

PATH RECORDING NODE INSERTION NODE FIND SURFACE NODE FORCE CONTROL NODE

SPECIFICATIONS	HAND-E	
Stroke (adjustable)	50 mm	2 in
Grip force (adjustable)	20 to 185 N	4.5 to 41 lbf
Form-fit grip payload	5 kg	11 lbs
Friction grip payload*	4,7 kg	8.8 lbs
Gripper mass	1 kg	2 lbs
Position resolution (fingertip)	0.2 mm	
Closing speed (adjustable)	20 to 150 mm/s	0.8 to 5.9 in/s
Communication protocol	Modbus RTU (RS-485)	
Ingress protection (IP) rating	IP67	

* Calculated for the use of silicon covered fingertips to grip a steel object, at a low robot acceleration.

** All specifications provided for reference only. See user manual at support.robotiq.com for official specifications.

WHAT'S NEXT?

Get access to the Adaptive Grippers specifications at **support.robotiq.com**



LEAN -ROBOTICS Chat with the Robotiq sales team: iss@robotiq.com 1-888-ROBOTIQ





Updated May 2020 robotiq.com

© Copyright Robotiq 2020